


SPRING INTO SMARTER PROTECTION

Wisualarm Fire Alarm
Clearance Promotion



WISUALARM FIRE ALARM OFFERS




Addressable Fire Alarm Control Panel

DHI-HY-1022R

- Reduce wiring costs and enhance circuit stability
- User-Friendly Display: The 4,3-inch LCD screen

R 3 773,74

Excl. VAT.



Addressable Fire Alarm Control Panel without Printer (Support max 508 devices)

DHI-HY-1025R

- Two-Wire, Polarity-Free Communication
- Extended Event Logging

R 5 484,86

Excl. VAT.




Addressable Manual Call Point (without base)

DHI-HY-1200

- Convenient wiring: Two-wire, polarity-free
- Ultra-low power consumption

R 79,18

Excl. VAT.



Addressable Heat Detector (without base)

DHI-HY-1310

- Detection performance: Accurate temperature detection by sensitive sensor

R 55,66

Excl. VAT.



Addressable Multi-sensor Smoke and Heat Detector (without base)

DHI-HY-1320

- Detection performance: Split-spectrum optical smoke sensor and sensitive thermistor

R 117,60

Excl. VAT.



Addressable Repeater Panel (with base)

DHI-HY-1330

- Suitable for residential and industrial buildings
- Ultra-low power consumption

R 235,98

Excl. VAT.



WISUALARM FIRE ALARM OFFERS

Addressable Input Module (without base)



DHI-HY-1400

- Simple installation: With a plug-in structure, easy to install and construct

R 67,42

Excl VAT.

Addressable InputOutput Module with Passive Output (without base)



DHI-HY-1410

- Ultra-low power consumption: Ultra-low monitoring current and alarm current

R 84,67

Excl VAT.

Isolator Module (without base)



DHI-HY-1431R

- Convenient wiring: Two-wire, polarity-free
- Reliable communication

R 109,76

Excl VAT.

Addressable Sounder Strobe (without base)



DHI-HY-1500

- Simple installation: With a plug-in structure, easy to install and construct

R 76,05

Excl VAT.

Addressable Manual Call Point for Fire Hydrant



DHI-HY-ANDZ

- Ideal for scenarios that require fire control rooms, such as residential communities, and other large public buildings.

R 14,11

Excl VAT.

Linear Beam Detector



DHI-HY-BD1

- Auto-alignment and manual alignment supported
- Direct integration with third-party detection systems

R 1 346,13

Excl VAT.

New Encoder



DHI-HY-BM-1712

- 360° panoramic overview in 12MP resolution
- Optimized for all lighting conditions

R 353,73

Excl VAT.

Conventional Fire Alarm Control Panel - 4 zones




DHI-HY-C102-4

- 90VAC to 270VAC main power supply ensures the stable operation
- 4 dry contacts

R 1 144,64

Excl VAT.

Conventional Fire Alarm Control Panel - 4 Zones without battery



DHI-HY-C102-4L

- Large cabinet
- Ethernet interfaces enables communication with IoT platform

R 1 514,69

Excl VAT.

Conventional Fire Alarm Control Panel - 8 Zones



DHI-HY-C102-8

- RS-485 interface contributes to convenient integration
- Record and export capacity of historical events for fire, fault & operation

R 1 582,11

Excl VAT.



WISUALARM FIRE ALARM OFFERS

Conventional Fire Alarm Control Panel - 8 Zones without battery



DHI-HY-C102-8L

- Large cabinet
- Ethernet interfaces enables communication with IoT platform

R 1 464,51

Excl VAT.

2-Wire Conventional Manual Call Point (with base)



DHI-HY-C121

- Simple installation: with a plug-in structure, easy to install and construct

R 79,18

Excl VAT.

2-Wire Conventional Smoke Detector (with base)



DHI-HY-C131

- Meets all requirements of latest EN54
- Two-wire, polarity-free realizes convenient wiring

R 67,42

Excl VAT.

2-Wire Conventional Heat Detector (with base)



DHI-HY-C132

- Auto-alignment and manual alignment supported
- Direct integration with third-party detection systems

R 55,66

Excl VAT.

2-Wire Conventional Sounder Strobe (with base)



DHI-HY-C151

- Ultra-low consumption and strong loading capacity
- Loud sound output over 75 dB(A) at 3 meters

R 76,05

Excl VAT.

Fire Alarm Bell



DHI-HY-C152

- High sound level
- Low current consumption

R 93,30

Excl VAT.

Fire Alarm Bell - 4 inch



DHI-HY-C153

- Alarm volume: Over 80dB (A) at 3 m
- Wall-mounted installation with Fire Safety certification

R 76,05

Excl VAT.

Sounder



DHI-HY-C154

- Standard voltage: 24VDC
- Easy to install and compatible with many fire alarm systems.

R 50,96

Excl VAT.

Red Strobe Light



DHI-HY-C155

- Loud and easily recognizable sound in emergency situations.
- Compact design with a striking red color

R 50,96

Excl VAT.

Environmental Sensor



DHI-HY-ES10A-R8

- 10-Year Battery Life: Set it up once and forget about annual replacements.
- Dual sensing for complete control

R 196,00

Excl VAT.



WISUALARM FIRE ALARM OFFERS



Flame Detection Network Camera

DHI-HY-FT121LDN

- Uncooled VOx thermal sensor technology
- Flame detection with adjustable and high sensitivity

R 1 552,00

Excl VAT.



Flame Detection Bullet Network Camera

DHI-HY-FT431LFP-TD1F4

- Industry leading uncooled VOx focal plane detector with high sensitivity
- Supports flame detection alarm

R 2 281,60

Excl VAT.

Wireless Interconnected Carbon Monoxide Alarm with Temperature and Humidity Detection



DHI-HY-GC30A-R8

- High-performance electrochemical CO sensor to deliver accurate detection of carbon monoxide leakage and respond quickly

R 247,20

Excl VAT.



Wireless Gateway (Lite)

DHI-HY-GW01A

- Support 4 LED indicators to illustrate the status of Power, Fault, Alarm and Internet Connectivity

R 453,60

Excl VAT.

Wireless Interconnected Heat Alarm



DHI-HY-HT10A

- Test and silence features in the central push button
- Loud sound output over 85 dB(A) at 3 meters

R 136,00

Excl VAT.

Wireless Interconnected Heat Alarm



DHI-HY-HT10A-R8

- Class A1 fire detection (54°C to 65°C)
- Silenced by a working infrared remote controller

R 148,00

Excl VAT.

Mains Powered Heat Alarm



DHI-HY-HT5MA

- Response times from typical application temperature
- Built-in 10-year rechargeable lithium battery back-up

R 264,80

Excl VAT.

Mains Powered Heat Alarm with 9V



DHI-HY-HT5MB

- Hardwire interconnection up to 24 units
- Wireless interconnected

R 188,00

Excl VAT.

Addressable Input Module DHI-HY-1400



DHI-HY-MKDZ2

- Ideal for scenarios that require fire control rooms, such as large public buildings.

R 25,09

Excl VAT.

Wireless Interconnected Module



DHI-HY-MRF50-R8

- Compatible with Wisualarm mains powered alarms
- Wireless interconnected with maximum of 24 WisuLink RF devices

R 110,40

Excl VAT.



WISUALARM FIRE ALARM OFFERS



Replaceable Battery Standalone Smoke Alarm

DHI-HY-SA20A

- Split-spectrum sensor technology
- Test and hush features in one single button

R 136,00

Excl VAT.



WiFi Smoke Alarm

DHI-HY-SA2FA

- Communication: 2.4GHz WiFi
- Compatible software: Wisualarm App

R 213,60

Excl VAT.



Wireless Interconnected Sealed Battery Smoke Alarm

DHI-HY-SA30A

- Split-spectrum sensor technology
- Low quiescent current consumption

R 136,00

Excl VAT.



Wireless Interconnected Sealed Battery Smoke Alarm

DHI-HY-SA30A-R8

- Loud sound output over 85 dB(A) at 3 meters
- Built-in battery, easy installation

R 148,00

Excl VAT.



Mains Powered Smoke Alarm

DHI-HY-SA5MA

- Silenced by a working infrared remote controller
- Built-in 10-year rechargeable lithium battery back-up

R 264,80

Excl VAT.



Mains Powered Smoke Alarm with 9V

DHI-HY-SA5MB

- Wireless interconnected with maximum of 24 devices,
- Test and silence features in the central push button

R 230,40

Excl VAT.



5MP IR AI-Fire Smoke Sensing Network Camerat

DHI-HY-SAV849HAP-ET

- Remote check based on smoke sensing and video alarm linkage
- Intelligent monitoring: Flame detection

R 1 200,80

Excl VAT.



Sounder Strobe Base

DHI-HY-SGDZ

- With a plug-in structure, easy to install and construct

R 14,11

Excl VAT.



Detector Base

DHI-HY-TCDZ

- Ideal for scenarios that require fire control rooms, such as large public buildings

R 13,35

Excl VAT.

LUNARX
CONSULTING AND PROJECTS

🌐 www.lunarx.co.za ☎ +27 (0) 11 266 7000

✉ info@lunarx.co.za

E&OE | Confirm stock availability to avoid disappointment. Free Delivery not available on sale items. Limited stock quantities available. All prices are VAT exclusive